



V80Q | PN | PLATE FIXING

RED POLYURETHANE TYRED WHEEL WITH NYLON CENTRE

80, 100, 125




160, 200



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
80	32	108	41	150	plain	V80Q 080 PNP P04	V81Q 080 PNP P04	V82Q 080 PNP P04
					roller	V80Q 080 PNR P04	V81Q 080 PNR P04	V82Q 080 PNR P04
100	32	128	41	150	plain	V80Q 100 PNP P04	V81Q 100 PNP P04	V82Q 100 PNP P04
					roller	V80Q 100 PNR P04	V81Q 100 PNR P04	V82Q 100 PNR P04
125	32	155	41	200	plain	V80Q 125 PNP P04	V81Q 125 PNP P04	V82Q 125 PNP P04
					roller	V80Q 125 PNR P04	V81Q 125 PNR P04	V82Q 125 PNR P04
160	45	200	55	350	plain	V80Q 160 PNP P05	V81Q 160 PNP P05	V82Q 160 PNP P05
					roller	V80Q 160 PNR P05	V81Q 160 PNR P05	V82Q 160 PNR P05
200	50	240	55	400	plain	V80Q 200 PNP P05	V81Q 200 PNP P05	V82Q 200 PNP P05
					roller	V80Q 200 PNR P05	V81Q 200 PNR P05	V82Q 200 PNR P05

V80Q | PN | SINGLE HOLE FIXING

RED POLYURETHANE TYRED WHEEL WITH NYLON CENTRE



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
80	32	108	41	150	plain	V80Q 080 PNP B12		V82Q 080 PNP B12
					roller	V80Q 080 PNR B12		V82Q 080 PNR B12
100	32	128	41	150	plain	V80Q 100 PNP B12		V82Q 100 PNP B12
					roller	V80Q 100 PNR B12		V82Q 100 PNR B12
125	32	155	41	200	plain	V80Q 125 PNP B12		V82Q 125 PNP B12
					roller	V80Q 125 PNR B12		V82Q 125 PNR B12

i All dimensions are in mm and all loadings are in kg unless otherwise stated