


VSL | EAP | PLATE FIXING


'ERGONOMIC' CROWN TREAD POLYURETHANE TYRED WHEEL WITH ALUMINIUM CENTRE



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
100	45	135	20	300	ball	VSL 100 EAPJ P05	VSLF 100 EAPJ P05	VSL 100 EAPJ P05 SWB
125	45	159	30	350	ball	VSL 125 EAPJ P05	VSLF 125 EAPJ P05	VSL 125 EAPJ P05 SWB
150	45	189	39	450	ball	VSL 150 EAPJ P05	VSLF 150 EAPJ P05	VSL 150 EAPJ P05 SWB
200	45	238	39.5	520	ball	VSL 200 EAPJ P05	VSLF 200 EAPJ P05	VSL 200 EAPJ P05 SWB

VSL | PT | PLATE FIXING

POLYURETHANE TYRED WHEEL WITH CAST IRON CENTRE



wheel diameter	tread width	fitted height	swivel offset	load capacity	bearing type	swivel	fixed	swivel + total-stop brake
100	49	135	20	350	ball	VSL 100 PTJ P05	VSLF 100 PTJ P05	VSL 100 PTJ P05 SWB
125	50	159	30	450	ball	VSL 125 PTJ P05	VSLF 125 PTJ P05	VSL 125 PTJ P05 SWB
150	50	189	39	600	ball	VSL 150 PTJ P05	VSLF 150 PTJ P05	VSL 150 PTJ P05 SWB
200	50	238	39.5	700	ball	VSL 200 PTJ P05	VSLF 200 PTJ P05	VSL 200 PTJ P05 SWB



WHEEL BRAKE
Swivel castors only

Simple side-mounted, foot operated brake acts upon the wheel only

Add **BK** to castor reference



4-WAY DIRECTIONAL LOCK for straight line travel

To suit all swivel castors except with total-stop brake

Add **DL** to castor reference

i All dimensions are in **mm** and all loadings are in **kg** unless otherwise stated